

XR940A Powered Air Purifying Respirator For Particulate Environments

XR940A is a battery powered air purifying respirator for protection against dust and particles. This system is TH3P certified in accordance with European standard EN12941: 1998/A 1:2004/A2:2008 TH3P

NEW



- XR940A supplies clean air reducing the effort required to breathe in fume environments. The electronic system for controlling the airflow monitors the blower in order to ensure a constant flow of min.170nl/min*. The operating time of XR940A with a fully charged battery depends on the & filter state but run time on the low setting is normally more than 11 hours & 9 hours on the high setting.
- Has enhanced warning signals, optical and audible alarms for low power, clogged filter and reduced airflow. The welding helmet features a multi adjustable headband with enhanced supports to spread the load evenly on the wearers head, vibration warning for low air flow.
- Comes with the XR937H true colour cartridge for enhanced clarity.
- Support provided by removable shoulder straps.



TECHNICAL DATA

AIR FLOW RATE	170 or 220nl/min Minimum
MATERIAL	PC + ABS
MOTOR	DC brushless
FUSE	Electronic
BATTERY	Li-ion 14.8V
BATTERY CHARGING TIME	Approx 2.5h
BATTERY LIFE EXPECTANCY	>350
RUN TIME	10 hour @ 170nl/min
NOISE	Max. 60dB(A)
VOLTAGE / CAPACITY	14.8V/2.2Ah
MASTER FILTER	P3 TH3P R SL
OPERATING TIME	1* 11h Operating time level 2* 9h (*min with a fully charged new battery & filter room temp.)
PRE FILTER	Active carbon (odour)
WEIGHT	288g (1097g incl. Filler and Battery)
DIMENSIONS	224 x 190 x 70 mm (MAX)
MASTER FILTER TYPE	P3 TH3P R SL for TH3P system (Europe)
APPROVALS	EN12941:1998/A1:2003/ A2:2008 TH3 P R SL

Filtration

The unit is fitted with a P3 Particulate main filter coupled with a carbon odour pre filter and a stainless steel spark trap to preserve the filters, all filters are replaceable. Filter lifetime is dependant upon the working environment. The unit is not suitable to operation in areas where the oxygen supply is depleted or there may be a risk of toxic gas build up.

- TH3P Protection factor 500
- TH3P filter applications
- Metal Grinding and cutting applications
- Welding of Aluminium by MIG or TIG process
- Welding of Stainless Steel MIG and TIG processes
- Welding of steel by MMA, MIG or TIG
- Welding of Zinc coated steel by MIG or TIG

SPARES INFORMATION

STOCK CODE	DESCRIPTION
XR940A	PAPR unit with carry bag, large view welding grinding helmet and universal charger
XR1002	Helmet
XR1003	Blower Unit
XR1004	Filter Cover
XR1005	Spark Arrestor
XR1006	Carbon Pre-filter
XR1007	P3 Hepa filter
XR1008	Waist Belt and Shoulder Harness
XR1009	Air Hose and Connectors
XR1010	FR Hose Cover
XR1011	Head Gear including Air Duct
XR1012	Sweat Band
XR1013	Head Gear Fixing Kit
XR1014	Face Seal and Fixings
XR1016	Battery
XR1017	Charger
XR9720	Inside Cover Lens
XR9730	Front Cover Lens

FEATURES:

Simple and clear status display

Smooth and ultra-quiet brushless motor

Variable airflow speed control

Removable Li/ion battery Run time 10hrs+

Easy to operate controls

Supplied with a P3 main filter, activated carbon pre filter and metal spark arrester

Light weight , less than 1.1kg



Sales: +44 (0) 1299 266800
E-Mail: info@parweld.co.uk



parweld
WELDING THE FUTURE