

## JALAS® 1625 E-SPORT

EN ISO 20345:2011, S3 SRC HI CI

### PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, good shock absorption, light

### SPECIFICATION

TYPE OF SHOE Safety footwear, boots/Ankle boots

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION E-Sport

PLATFORM M-Sport

UPPER MATERIAL PU-coated leather, split leather

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Classic

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, shock absorption zone in Ergothan

FASTENING Laces

COLOUR Black, grey, red



SIZE	ART. NO.	EAN NO.
36	1625-36	6408487438639
37	1625-37	6408487438646
38	1625-38	6408487438653
39	1625-39	6408487438660
40	1625-40	6408487438677
41	1625-41	6408487438684
42	1625-42	6408487438691
43	1625-43	6408487438707
44	1625-44	6408487438714
45	1625-45	6408487438721
46	1625-46	6408487438738
47	1625-47	6408487438745

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## JALAS® 1625 E-SPORT

### FEATURES

Low weight, oil-resistant outsole, anti-static properties, bellows tongue, padded boot shaft, ventilating insole, water repellent, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

### PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

### PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration



Aluminium toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-12-12

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## JALAS® 1625 E-SPORT

**COMPLIANCE**  
EN ISO 20345:2011

### COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-resistant upper

P: Penetration-resistant outsole

CI: Cold insulation

HI: Heat insulation

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 121-119: Orthopedic footwear adjustment according to German DGUV 121-119. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-12-12

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com