



jalas® GRAN PREMIO 1668W

EN ISO 20349-2:2017 S3, SRC, WG, HRO, CI, HI ASTM F2413-18 M/I/C PR



Learn more

WELDING BOOT WITH MANY FEATURES

Durable and comfortable mid-cut welding boot certified in compliance with EN 20349-2, with Thinsulate™ lining for extra heat protection. The leather upper is PU-coated and the KEVLAR thread in the seams resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit). The oil and heat-resistant nitrile outer sole means excellent grip and JALAS® aluminium toe cap, steel nail penetration insert and two impact protection zones in PORON® XRD® help prevent injuries.

CHARACTERISTICS	FUNCTIONS	
• Highest level of protection • Excellent grip • Perfect fit • Extra comfortable • Excellent shock absorption	• ProNose toe reinforcement • Pull loops • ESD • Water repellent • KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit) • Easy clean upper • Ventilating insole • Thinsulate™ heat insulation • Wide fit	• Heat-resistant upper • Heat-resistant outsole • Oil-resistant outsole • Anti-static properties • Padded boot shaft • Double shock absorption zones



PREVENTS RISK OF

toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

outdoors, indoors, all-year use, warm surfaces,
environments with risk for outsole penetration, dirty
environments, harsh environments

PRIMARY AREAS OF USE

hot work, metalwork, sheet-metal work, welding

PRIMARY INDUSTRIES OF USE

metal fabrication

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Steel

FITTING Wide

COLLECTION Gran Premio

UPPER MATERIAL PU-coated leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, Thinsulate™

INSOLE FX2 Pro

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-
based conductive thread, Double shock absorption zones
in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING Hook-and-loop


COLOUR Black

NET WEIGHT, (SIZE 42) 1.34 kg

COMPLIANCE










TP TC 019:2011



EN ISO 20349-2:2017
S3, SRC, WG, HRO, CI, HI

ASTM F2413-18
M/I/C
PR

FEATURES



SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	1668W-36	6408487542022
37	4	5	6	1668W-37	6408487541537
38	5	5½	6½	1668W-38	6408487541575
39	6	6½	7½	1668W-39	6408487541612
40	6½	7½	8½	1668W-40	6408487541650
41	7	8	9	1668W-41	6408487541698
42	8	9	10	1668W-42	6408487541735
43	9	9½	11	1668W-43	6408487541773
44	10	10½	11½	1668W-44	6408487541810
45	10½	11	12½	1668W-45	6408487541858
46	11	12	13	1668W-46	6408487541896
47	12	13	14	1668W-47	6408487541933
48	13	13½	14½	1668W-48	6408487541971

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com